



# RUBIA 2500 20W40



Multigrade diesel engine oil.

## APPLICATIONS

- For all naturally aspirated or super charged diesel engines operating under severe conditions.
- Can be used for old vehicles (off road) and DG sets.

## SPECIFICATION

- API CF
- MACK T8A
- IS 13656 :1993 EDL3

## ADVANTAGES

- Exhibit good viscosity stability throughout oil life
- Render very good film forming characteristics during operation
- Demonstrate resistance against soot agglomeration and oil thickening
- Excellent antiwear and anti corrosion properties protects engine
- Infused with antioxidant, antirust, antifoaming additive for a smoother and trouble free operation

TYPICAL CHARACTERISTICS	TEST METHOD ASTM	RUBIA 2500 20W40
Density at 29.5°C, kg/l	D 4052	0.871
Kinematic viscosity at 100°C, cSt	D 445	14.79
Viscosity Index	D 2270	116
Pour point, °C	D 97	-24
Total Base Number, mg KOH/g	D 2896 (B)	6.3
Flash point COC, °C	D 92	244

(Above characteristics are mean values given as an information)

### TOTAL OIL INDIA PVT LTD.

Head Office : 3<sup>rd</sup> Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720  
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,  
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from : [www.total.co.in](http://www.total.co.in)

Date 01/12