



RUBIA TIR 6400 15W40 TOTAL

High quality lubricant for diesel engines.

APPLICATIONS

All industrial vehicles

All types of services

- Particularly suitable for the most modern Diesel engines fitted on trucks, buses, construction or agricultural machinery, with or without turbo compressors, intercoolers or sophisticated injection systems.
- Can handle the most demanding applications: transports, public works...

SPECIFICATION

OEM APPROVALS

ACEA	E5/ E3
API	CH-4/SJ
MERCEDES	MB-Approval 28.3
MAN	M 3275
VOLVO	VDS-2
MTU OIL	Type 2
RENAULT TRUCKS	RD / RD-2
MACK	EOM
CUMMINS	CES 20076
ZF	TE-ML 04C

ADVANTAGES

Technical performances

- Proven technology – Demonstrated its versatility when used in construction sites for > five hundred hours and several thousand km on the roads in varied operating condition.
- Very high protection against wear, in all conditions of services, thus guaranteeing an extended engine lifespan.
- Very high dispersancy and detergency levels: prevents clogging and reduces down time and filter change frequency

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from www.quick-fds.com ; www.total.co.in

Date 01/12



RUBIA TIR 6400 15W40 **TOTAL**

- Lower CCS (cold cranking simulation) value helps in easy starting and quick flow of oil to critical parts irrespective of their location (Turbo on the top) in engine thus reduces engine wear and energy wastage

TYPICAL CHARACTERISTICS	TEST METHOD ASTM	RUBIA TIR 6400 15W40
Density at 29.5°C, kg/l	D 4052	0.869
Kinematic viscosity at 100°C, cSt	D 445	14.54
Viscosity Index	D 2270	136
Pour point, °C	D 97	-27
Total Base Number, mg KOH/g	D 2896 (B)	9.6
Flash point COC, °C	D 92	>200

(Above characteristics are mean values given as an information)

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from www.quick-fds.com ; www.total.co.in

Date 01/12