



RUBIA TIR 7200 FE 15W30



High quality lubricant for diesel engines with the Fuel Economy technology benefits.

APPLICATIONS

All industrial vehicles

All types of services

Environment

- Developed in cooperation with the transport industry, this competitive lubricant can significantly reduce fuel consumption particularly. When used with the Fuel Economy transmission lubricants, it can reduce fuel consumption by about 1L / 100 km
- Can handle the most demanding applications: deliveries, frequent stops, construction sites, harvesting ...
- Suitable for EURO 5 and previous engines (except EURO 4 and 5 of MAN and DAF engines)

SPECIFICATION

OEMS' approvals

ACEA	E5 / E7
API	CI-4
GLOBAL DHD-1	
RENAULT TRUCKS	RLD-2
MERCEDES	MB-Approval 228.3
MAN	M 3275
CUMMINS	CES 20071/20072/20077/20078
VOLVO	VDS-3
MACK	EO-M+

ADVANTAGES

Fuel savings

Technical perform

- New age technology helps in reducing the fuel consumption by about 1L/100 km.
- Superior technology helps in maintaining optimum film thickness even in such low viscometrics. Thus renders very high protection against wear, in all conditions of services, hence guaranteeing an extended engine lifespan.
- Very high dispersancy and detergency levels: prevents clogging, thus reduces filter change and down time.

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from www.quick-fds.com ; www.total.co.in

Date 01/12



RUBIA TIR 7200 FE 15W30



TYPICAL CHARACTERISTICS	TEST METHOD ASTM	RUBIA TIR 7200 FE 15W30
Density at 29.5°C, kg/l	D 4052	0.869
Kinematic viscosity at 100°C, cSt	D 445	12.1
Viscosity at 40°C, cSt	D 445	84.16
Viscosity Index	D 2270	138
Pour point, °C	D 97	-27
Total Base Number, mg KOH/g	D 2896 (B)	10.5
Flash point COC, °C	D 92	>200

(Above characteristics are mean values given as an information)

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from www.quick-fds.com ; www.total.co.in

Date 01/12