



DYANATRANS SF 3I



Universal oil for transmission and hydraulic systems of farm tractors and construction machinery equipped with wet disc brakes.

APPLICATIONS

- Mechanical transmissions of tractors and construction machineries requiring GL4 level product.
- Drive axles equipped with wet brakes which are prone to "squawk" and vibration.
- Suitable for spur or planetary drives.
- Can be used for power take offs, hydraulic lift, servo, transmission and steering system ... etc.

SPECIFICATION

- FORD M2C134D
- MASSEY FERGUSON CMS M 1141/1135
- JOHN DEERE J 20C/20D,
- JI CASE MS 1206,
- API GL 4

ADVANTAGES

- Infusion of anti-wear additives helps in extending the life of hydraulic and transmission components.
- Excellent protection against rust and corrosion even in the presence of water.
- Optimised film thickness helps in efficient, quiet and gradual braking. Thus reduces chattering and squawks
- Exhibit higher oxidation stability and good thermal resistance
- Excellent seal compatibility
- Good anti-foam characteristics

TYPICAL CHARACTERISTICS	TEST METHOD ASTM	DYANATRANS SF 3I
Density at 29.5°C, kg/l	D 4052	0.876
Kinematic viscosity at 100°C, cSt	D 445	10.59
Viscosity at 40°C, cSt	D 445	86.83
Viscosity Index	D 2270	105
Pour point, °C	D 97	-27

(Above characteristics are mean values given as an information)

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from [: www.total.co.in](http://www.total.co.in)

Date 01/12