



MULTIS XL 3



Multipurpose Extra Life lithium grease.

APPLICATIONS

Multi purpose grease

General lubrication

Recommendation

- MULTIS XL 3 is multipurpose grease for general lubrication of all kinds of universal applications in transport, agriculture and off road equipment, heavy industries : Steel works, quarry and civil engineering equipment operating in wet, dusty and/or dry conditions.
- Can be used for the operational temperature ranging -20 to 120 deg c.
- Pre-eminently suitable for passenger car, light truck and leisure vehicle applications.
- Always avoid contamination of grease by dust and/or dirt
- Preferably use a pneumatic pump system or cartridges.

SPECIFICATION

- ISO 6743-9: L-XBCEA 3
- DIN 51502: K3K -20

ADVANTAGES

Stable Structure

Oxidation Resistance

Water Resistance

- MULTIS XL 3 renders stable structure even under prolonged mechanical stresses and at high temperature by retaining its consistency thus avoids ejection and loss of consistency during operation.
- Multis XL 3 offers very good resistance to oxidation enabling long service life without any change in physical properties.
- Multis XL 3 exhibit excellent water resistance characteristics
- Multis XL 3 is infused with high level of anti wear and lubricity additive thus render very good retention of the film to reduce friction and bearing failure.
- Multis XL 3 demonstrates good rust and corrosion resistance property even in the presence of water and humid environment.

TYPICAL CHARACTERISTICS	TEST METHOD ASTM	MULTIS XL 3
Texture	---	Smooth
Colour	Visual	Cream to Pale Yellow
Drop Point, °C	D 566	> 180
Worked Penetration 60 strokes @25 °C, mm	D 217	220 -250
NLGI Grade	---	3
Base oil Viscosity @ 40 °C , cSt	D 445	150
Flash point COC, °C	D 92	234

(Above characteristics are mean values given as an information)

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720

Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,

Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from : www.total.co.in

Date 01/12